

CHALLENGER

600·601·604·605·650

Note:
This chart shows the general layout of the Challenger 600/601/604/605/650 standard version. The arrangement and number of the individual items may vary.

Crash Crew Chart

REVISION 5

TECHNICAL PUBLICATIONS AND INFORMATION - Copyright © 2015 by Bombardier Inc. All rights reserved.

General Information	
Maximum Capacity	
Passenger	Crew
12	3
Maximum Fuel Capacity	
20 000 lbs (9 072 kg)	
2 468 US gal (11 213 L)	

Aircraft Dimensions

WARNING
DO NOT ATTEMPT TO CHOP THROUGH WINDOWS

Cut Here in Emergency

Type III Overwing Emergency Exit

APU and Engine

DANGER

Idle Power

ZONES

- ENGINE
- APU

Engine/APU Shutdown

CHALLENGER 600

CHALLENGER 601

CHALLENGER 604·605·650

Service Doors and Panels

Passenger Door (Upward Opening)

WARNING
CABIN MAY BE PRESSURIZED

1. Press release button, handle will spring out
2. Turn handle CCW
3. Pull up to open

Passenger Door (Downward Opening)

WARNING
CABIN MAY BE PRESSURIZED

1. Press release button, handle will spring out
2. Turn handle CCW
3. Pull up to open

WARNING
USE ONLY DRY POWDER OR CLASS ★ FIRE EXTINGUISHERS ON BRAKE/WHEEL FIRES.

DANGER
TIRE MAY EXPLODE. APPROACH FROM FORWARD OR AFT WHEN FIGHTING WHEEL FIRE.

Wheel/Brake Fire

WARNING
FOR BRAKE/WHEEL FIRES, USE ONLY DRY POWDER OR CLASS ★ FIRE EXTINGUISHERS. FOR ALL OTHER PARTS OF THE AIRCRAFT, USE CLASS B OR C FIRE EXTINGUISHERS.

BAGGAGE COMPARTMENT DOOR

1. Press release button, handle will spring out
2. Turn handle CCW
3. Push door inward and upward

Aft Equipment and APU Compartment Fire

1. Press release button, handle will spring out
2. Turn handle CCW
3. Support door and open

Rear Fuselage Equipment Bay Door

1. Press release button, handle will spring out
2. Turn handle CCW
3. Support door and open